



PRODUCT DATA SHEET

Quality Products and Service Since 1964

GRAPHITE POWDER

PRODUCT DESCRIPTION:

Lub-O-Seal Graphite Powders are very fine black powders that offer good lubrication properties for a variety of applications. Graphite powder can be used as a dry lubricant in its original form or as a lubrication additive in greases, oils or colloidal solutions. Graphite contains high levels of carbon and therefore offers good electrical conductivity.

APPLICATIONS:

Use as a dry lubricant for locks, hinges, latches, sliding surfaces, threaded fittings, chains, sprockets, gears, electrical connectors, knife-type disconnect switches, spark plug threads, etc. Use as a lubricant or high temperature additive when combined with oils, greases, solvents, water or other materials.

DATA & SPECIFICATIONS:

<u>Grade</u>	<u>Graphite Type</u>	<u>Typical Particle Sizing</u>	<u>Carbon</u>
076	Amorphous, Natural	90% - 200 Mesh / 75 Micron	72%
A99	Synthetic	97% - 325 Mesh / 44 Micron	99%

Useful Temperature Range: -297°F to +2400°F

WARRANTY INFORMATION - PLEASE READ CAREFULLY

Lub-O-Seal Company, Inc. believes that the information in this publication is an accurate description of the typical characteristics and/or uses of the product, but it is your responsibility to thoroughly test the product in your specific application in order to determine its performance, efficacy and safety. Lub-O-Seal specifically disclaims any other expressed or implied warranty, including warranties of merchantability and of fitness for a particular use. Your exclusive remedy and Lub-O-Seals sole liability for breach of warranty is limited to the refund of the purchase price or the replacement of the product shown to be other as warranted, and Lub-O-Seal expressly disclaims any liability for incidental or consequential damages.

Lub-O-Seal Company, Inc. • 17519 Lewis Drive • Cypress, Texas 77433 - USA
Visit us on the Internet: www.Lub-O-Seal.com